


# Standsschränke aus Polyester

## Montageplatten



### Hinweis:

Abmessungen, siehe [Seite 199](#)

Ausführung	Montageplatten ohne Aussparung	Lochplatte Telequick
	<ul style="list-style-type: none"> <li>Direkte Montage auf M8-Einsätzen an der Rückseite des Gehäuses oder auf Verstellschienen zur Tiefeneinstellung (siehe <a href="#">Seite 194</a>). Die Gehäuse mit einer Höhe <math>\geq 1000</math> mm haben Zwischenabdrücke für die Installation von Montageplatten mit einer geringeren Höhe (M8-Einsätze, Artikel-Nr. <b>NSYTEX8</b>, separat zu bestellen).</li> <li>In Gehäusen mit 2 Türen können 1 komplette Montageplatte oder 2 einzelne Montageplatten eingebaut werden.</li> </ul>	<ul style="list-style-type: none"> <li>Gitter mit Bohrlöchern (11 x 26 mm), mit einem Schritt von 15 x 30 mm, für die direkte Installation, mit Klippmuttern, aller Geräte mit einer Befestigung an 2, 3 oder 4 Punkten, mit Schrauben mit einem Durchmesser von 3, 4, 5 oder 6 mm.</li> <li>Direkte Montage auf M8-Einsätzen an der Rückseite des Gehäuses oder auf Verstellschienen zur Tiefeneinstellung (siehe <a href="#">Seite 194</a>). Die Gehäuse mit einer Höhe <math>\geq 1000</math> mm haben Zwischenabdrücke für die Installation von Montageplatten mit einer geringeren Höhe (M8-Einsätze, Artikel-Nr. <b>NSYTEX8</b>, separat zu bestellen).</li> </ul>
Material	Verzinktes Stahlblech	Verzinktes Stahlblech
Finish	–	–
Farbe	–	–
Stärke	2,5 mm	–
Max. Belastung	150 kg/m <sup>2</sup>	150 kg/m <sup>2</sup>
Lieferumfang	1 Montageplatte	1 Montageplatte

9

Abmessungen					Abmessungen			
Höhe (A) (mm)	Breite (B) (mm)	H (mm)	Fläche (dm <sup>2</sup> )	Artikel-Nr.	E (mm)	D (mm)	Surface (dm <sup>2</sup> )	Artikel-Nr.
500	500	-	14	<b>NSYPMM55</b>	350	350	13	<b>NSYPMR55</b>
500	750	-	24	<b>NSYPMM75</b>	350	600	23	<b>NSYPMR57</b>
500	1000	437,5	32	<b>NSYPMM510</b>	350	2 x 350	26	<b>2 x NSYPMR55</b>
500	1250	-	38	<b>NSYPMM55+ NSYPMM75</b>	350	350 + 600	36	<b>NSYPMR55 + NSYPMR57</b>
750	500	-	24	<b>NSYPMM75</b>	600	350	23	<b>NSYPMR75</b>
750	750	-	40	<b>NSYPMM77</b>	600	600	38	<b>NSYPMR77</b>
750	1000	437,5	54	<b>NSYPMM710</b>	600	2 x 350	46	<b>2 x NSYPMR75</b>
750	1250	687,5	70	<b>NSYPMM712</b>	600	350 + 600	61	<b>NSYPMR75 + NSYPMR77</b>
1000	500	-	33	<b>NSYPMM105</b>	850	350	32	<b>NSYPMR105</b>
1000	750	-	55	<b>NSYPMM107</b>	850	600	54	<b>NSYPMR107</b>
1000	1000	437,5	74	<b>NSYPMM1010</b>	850	2 x 350	64	<b>2 x NSYPMR105</b>
1000	1250	687,5	96	<b>NSYPMM1012</b>	850	350 + 600	86	<b>NSYPMR105 + NSYPMR107</b>
1250	500	-	42	<b>NSYPMM125</b>	1100	350	42	<b>NSYPMR125</b>
1250	750	-	70	<b>NSYPMM127</b>	1100	600	70	<b>NSYPMR127</b>
1250	1000	437,5	96	<b>NSYPMM1210</b>	1100	2 x 350	84	<b>2 x NSYPMR125</b>
1250	1250	687,5	124	<b>NSYPMM1212</b>	1100	350 + 600	112	<b>NSYPMR125 + NSYPMR127</b>
1500	500	-	51	<b>NSYPMM155</b>	1350	350	51	<b>NSYPMR155</b>
1500	750	-	85	<b>NSYPMM157</b>	1350	600	85	<b>NSYPMR157</b>
1500	1000	437,5	118	<b>NSYPMM1510</b>	1350	2 x 350	102	<b>2 x NSYPMR155</b>
1500	1250	687,5	152	<b>NSYPMM1512</b>	1350	350 + 600	136	<b>NSYPMR155 + NSYPMR157</b>
2000	750	-	115	<b>NSYPMM207</b>	2 x 850	2 x 600	108	<b>2 x NSYPMR107</b>

Metal mounting plate



**Note:**

For dimensions see [page 215](#)



Characteristics	Plain mounting plate	Telequick mounting plate
	<ul style="list-style-type: none"> <li>Direct installation on M8 inserts at the rear of the enclosure or on step slides for depth adjustment (see <a href="#">page 210</a>). The enclosures with height of <math>\geq 1000</math> mm have intermediate impressions for installing mounting plates of a lesser height (M8 inserts, ref. <b>NSYTEX8</b>, to be ordered separately).</li> <li>In the two door enclosures, it is possible to install one complete mounting plate or two individual mounting plates.</li> </ul>	<ul style="list-style-type: none"> <li>Grille with 11 x 26 mm drill holes, with a step of 15 x 30 mm, for direct installation, with clip nuts, of all the devices with fixing at 2, 3 or 4 points, by screws with diameters of 3, 4, 5 or 6 mm.</li> <li>Direct installation on M8 inserts at the rear of the enclosure or on step slides for depth adjustment (see <a href="#">page 210</a>). The enclosures with height of <math>\geq 1000</math> mm have intermediate impressions for installing mounting plates of a lesser height (M8 inserts, ref. <b>NSYTEX8</b>, to be ordered separately).</li> </ul>
<b>Material</b>	Galvanized sheet steel	Galvanized steel
<b>Finish</b>	—	—
<b>Color</b>	—	—
<b>Thickness</b>	2.5 mm	—
<b>Maximum load</b>	150 kg/m <sup>2</sup>	150 kg/m <sup>2</sup>
<b>Supply</b>	One mounting plate	One mounting plate

## 9 PLA

Dimensions					Dimensions			
Height (A) (mm)	Width (B) (mm)	H (mm)	Surface (dm <sup>2</sup> )	References	E (mm)	D (mm)	Surface (dm <sup>2</sup> )	References
500	500	-	14	NSYPMM55	350	350	13	NSYPMR55
500	750	-	24	NSYPMM75	350	600	23	NSYPMR57
500	1000	437.5	32	NSYPMM510	350	2 x 350	26	2 x NSYPMR55
500	1250	-	38	NSYPMM55 + NSYPMM75	350	350 + 600	36	NSYPMR55 + NSYPMR57
750	500	-	24	NSYPMM75	600	350	23	NSYPMR75
750	750	-	40	NSYPMM77	600	600	38	NSYPMR77
750	1000	437.5	54	NSYPMM710	600	2 x 350	46	2 x NSYPMR75
750	1250	687.5	70	NSYPMM712	600	350 + 600	61	NSYPMR75 + NSYPMR77
1000	500	-	33	NSYPMM105	850	350	32	NSYPMR105
1000	750	-	55	NSYPMM107	850	600	54	NSYPMR107
1000	1000	437.5	74	NSYPMM1010	850	2 x 350	64	2 x NSYPMR105
1000	1250	687.5	96	NSYPMM1012	850	350 + 600	86	NSYPMR105 + NSYPMR107
1250	500	-	42	NSYPMM125	1100	350	42	NSYPMR125
1250	750	-	70	NSYPMM127	1100	600	70	NSYPMR127
1250	1000	437.5	96	NSYPMM1210	1100	2 x 350	84	2 x NSYPMR125
1250	1250	687.5	124	NSYPMM1212	1100	350 + 600	112	NSYPMR125 + NSYPMR127
1500	500	-	51	NSYPMM155	1350	350	51	NSYPMR155
1500	750	-	85	NSYPMM157	1350	600	85	NSYPMR157
1500	1000	437.5	118	NSYPMM1510	1350	2 x 350	102	2 x NSYPMR155
1500	1250	687.5	152	NSYPMM1512	1350	350 + 600	136	NSYPMR155 + NSYPMR157
2000	750	-	115	NSYPMM207	2 x 850	2 x 600	108	2 x NSYPMR107